

Material Safety Data Sheet: FlameSAFE Carbon Dioxide**1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER****Product Name:**

FlameSAFE Carbon Dioxide

Product Use:

The intended or recommended use is as a Fire Extinguishing Agent.

Chemical Formula: CO₂**Manufacturer/Supplier:**

AMPAC Safety Pty Ltd

7 Ledger Road, Balcatta, WA 6021

Ph: +619 9200 2100

Emergency Ph: +61408022433

2. HAZARDS IDENTIFICATION**Hazard classification:**

Not classified as hazardous according to NOHSC criteria. Classified as a dangerous good by the criteria of the ADG code.

Hazards identification:

Liquefied gas. Contact with liquid may cause coldburns / frostbite.

3. COMPOSITION / INFORMATION ON INGREDIENTS**Substance / Preparation:** Substance**Substance Name:** Carbon Dioxide**Contents:** 100%**CAS No:** 124-36-9**EC No:** 204-696-9

Contains no other components or impurities which will influence the classification of the product

4. FIRST AID MEASURES**Inhalation:**

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Low concentrations of CO₂ cause increased respiration and headache. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Skin/Eye Contact:

FlameSAFE Carbon Dioxide Fire Extinguisher

Immediately flush eyes thoroughly with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.

Ingestion:

Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

5. FIRE-FIGHTING MEASURES**Flammable Class:**

Non Flammable.

Specific Hazards:

Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products:

None.

Extinguishing media:

This preparation is an extinguishing media. Use media appropriate for surrounding materials.

Specific Methods:

If possible, stop flow of product. Move away from the container and cool with water from a protected position. If leaking do not spray onto container. Water surrounding area from protected position to contain fire.

Special protective equipment for Fire fighters:

In confined space use self-contained breathing apparatus.

Material Safety Data Sheet: FlameSAFE Carbon Dioxide

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Evacuate area. Use protective clothing. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation.

Environmental precautions:

Try to stop release. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Clean up methods:

Ventilate area.

7. HANDLING AND STORAGE

General:

Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Potential production of solid CO₂ particles must be ruled out. In order to rule out potential electrostatic discharge production, the system must be adequately grounded.

Storage:

Keep container below 50°C in a well ventilated place.

Handling:

Suck back of water into the container must be prevented. Do not allow backfeed into the container. Use only properly specified equipment which is suitable for this product. Its supply pressure and temperature. Contact your gas supplier if in doubt. Refer to supplier's container handling instructions.

NOTE: The handling and storage information above applies to FlameSAFE Carbon Dioxide stored in cylinders and not when contained in a stored-pressure fire extinguisher. When stored in a stored-pressure fire extinguisher ensure good housekeeping practices, store below 50°C and avoid dropping or severe impacts.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection:

Ensure adequate ventilation. Protect eyes, face and skin from liquid splashes.

Occupational Exposure Limits:

Carbon dioxide: ILV (EU) –8H – (mg.m³) : 9000

Carbon dioxide: ILV (EU) – 8H (ppm) : 5000

Carbon dioxide: TLV – TWA (ppm) : 5000

Carbon dioxide: TLV – STEL (ppm) : 30000

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State at 200C:	Liquefied Gas
Colour:	Colourless
Odour:	No odour warning properties
Molecular weight:	44
Melting point (C):	56.6
Boiling point (C):	-78.5 (s)
Critical temperature:	30
Vapour pressure:	57.3 bar
Relative density, gas (air=1):	1.52
Relative density, liquid (water = 1):	1.03
Solubility in water (mg/l):	2000
Flammability range (vol% in air):	Non flammable

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

10. STABILITY AND REACTIVITY

Stability and reactivity:

Stable under normal conditions. Liquid spillages can cause embrittlement of structural materials.

11. TOXICOLOGICAL INFORMATION

Toxicity information:

In high concentrations cause rapid circulatory insufficiency. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness.

12. ECOLOGICAL INFORMATION

Ecological effects information:

When discharged in large quantities may contribute to the greenhouse effect. Can cause frost damage to vegetation.

Global warming potential(CO₂=1): 1

13. DISPOSAL CONSIDERATIONS

General:

Do not discharge into any place where its accumulation could be dangerous. Discharge to atmosphere in large quantities should be

Material Safety Data Sheet: FlameSAFE Carbon Dioxide

avoided. Contact supplier if guidance is required.

14. TRANSPORT INFORMATION

UN No: 1013
Labelling ADG: Label 2.2: Non flammable, non toxic gas.
H.R. nr: 20
Proper Shipping Name: Carbon Dioxide

HAZCHEM

- **Emergency Action Code:** HAZCHEM, HAZCHEM_C
- **ADG Class:** 2
- **ADG Classification code:** 2 A

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

- ensure that containers are firmly secured
- ensure there is adequate ventilation
- compliance with applicable regulations

NOTE: The transportation information above applies to FlameSAFE Carbon Dioxide as shipped in cylinders and not when contained in a stored-pressure fire extinguisher. When shipped in a stored-pressure fire extinguisher the fire extinguisher is considered Class 2.2 (Non-Flammable, Non-Toxic Gas) Dangerous Goods. The Proper Shipping Name shall be FIRE EXTINGUISHERS and the UN designation UN1044.

15. REGULATORY INFORMATION

EC Classification:

Not included in Annex I. Not classified as dangerous preparation/substance.

EC Labelling: No EC labelling required
Symbol(s): None
R Phrase(s): None
S Phrase(s): None

16. OTHER INFORMATION

- Asphyxiant in high concentrations

- May cause frostbite
- Keep container in a well-ventilated place
- Do not breathe the gas
- Ensure all national/local regulations are observed
- The hazard of asphyxiation is often overlooked and must be stressed during operator training

DISCLAIMER OF LIABILITY:

The Information contained herein is furnished without warranty either expressed or implied. This data sheet is not a part of any contract of sale. The information contained herein is believed to be correct or is obtained from sources believed to be generally reliable. However, it is the responsibility of the user of these materials to investigate, understand and comply with the federal and state guidelines and procedures for safe handling and use of these materials. AMPAC Safety Pty Ltd shall not be liable for any loss or damage arising directly or indirectly from the use of this product and AMPAC Safety Pty Ltd assumes no obligation or liabilities for reliance on the information contained herein or omissions from 25th October 2013.

Document Issue Date: 30th October 2013

End MSDS

